# **FAN BLADE EDGES REBUILT WITH BELZONA**

ID: 328

Industry: Power Dower Power Plant in Mississippi, USA

Application: FBC-Fans, Blowers and Compressors Application Date: February 2002

Substrate: Fiberglass

Products: \* Belzona® 1321 (Ceramic S-Metal),

#### **Problem**

Erosion of both the leading and trailing edges of cooling tower fan blades, caused inefficient tower operation and raised concerns about blade replacement in the near future.









# **Photograph Descriptions**

- \* View of the huge cooling tower,
- \* Close-up of the fan blade damage,
- \* Application with small roller,
- \* Finished application ,

### **Application Situation**

Cooling tower fan blade edges.

## **Application Method**

The application was carried out in accordance with Belzona Know-How System Leaflet FBC-1.

#### **Belzona Facts**

This huge cooling tower has ten individual cells. Each cell contains eight cooling tower blades, and all ten cells were refurbished with the afore-mentioned Belzona Know-How technique.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®

Repair • Protect • Improve