BELZONA REPAIR TO OIL COOLER

ID: 366

Industry: Power Station in Sri Lanka

Application: HEX-Heat Exchangers Application Date: January 2001

Substrate: Copper Alloy

Products: * Belzona® 1111 (Super Metal),

* Belzona® 1321 (Ceramic S-Metal),

Problem

The unit was severely damaged and leaking as a result of bimetallic corrosion.









Photograph Descriptions

- * Corroded unit with holes clearly visible Belzona® 1111 being used to repair holed and corroded areas,
- * Belzona® 1321 being applied to protect unit,
- * Completed application being pressure tested,

Application Situation

Thrust bearing oil cooler from turbine

Application Method

Application was carried out using techniques adapted from Belzona System Leaflets HEX-3 & HEX-9. Holed and corroded areas were rebuilt using Belzona® 1111 incorporating Belzona® 9341 (Reinforcement Tape).

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

Belzona Facts Unit was pressure tested before being returned to service and has regularly been inspected since and remains in perfect condition. Belzona repair was carried out at a fraction the cost of a replacement unit.