BIG SAVINGS WITH BELZONA'S UNCONVENTIONAL REPAIR TECHNIQUES

ID: 372

Industry: Chemical & Petrochemical Customer Location: Petrochemical facility - Minnesota, U.S.A.

Application: GSS-Gaskets, Seals and Shims Application Date: June 2001

Substrate: Steel & Concrete

Products: * Belzona® 4151 (Magma-Quartz Resins),

Problem

Hollow spots under pump base between the grout and the steel base created vibration, thereby causing pre-mature bearing failure.







Photograph Descriptions

- * Removal of pump from base,
- * Installing injection ports,
- * Injecting with gun ,

Application Situation

Bearing failure in pump from vibration.

Application Method

The Application was carried out in accordance with a modified version of Belzona Know-How Systems leaflet GSS-9. Injection Method: Product placed in pneumatic gun, injected using static mixer.

Belzona Facts

This can be completed for 1/10th the cost of rebuilding and regrouting the pump base. Application is so successful, over 200 pump bases have been done at this facility.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

