

BELZONA® 1521 PROTECTS OIL/GAS/WATER SEPARATOR

ID: 442

Industry: Oil & Gas

Application: VPF-Valves, Pipes and Fittings

Substrate: Steel

Products: * Belzona® 1391 (Ceramic HT Metal) Belzona® 1521 (HTS1 Metal) ,

Customer Location: North Sea Oil & Gas Producer

Application Date: April 2004

Problem

Corrosion of the equipment caused by failure of the existing lining system required complete removal of the coating.



Photograph Descriptions

- * Stripe coating of welds, nozzles and brackets ,
- * Completed upper half of vessel ,
- * Completed weir area and brackets ,

Application Situation

Corrosion of oil / gas / water separator.

Application Method

Following grit blasting, stripe coating was completed using Belzona® 1391 for all nozzles, welds and brackets. Following reblasting Belzona® 1521 was applied using heated airless spray.

Belzona Facts

The use of Belzona® 1521 allows applications to be carried out at low temperatures offering a rapid application and return to service time for process vessels operating at elevated temperature. Belzona® 1522 (HTS2 Metal) could have been used for this application. Its designed for plural airless spray application.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015

FS 695214

ISO 14001:2015

EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA®
Repair • Protect • Improve