BELZONA REPAIRS AND COATS PUMP CASE

ID: 5228

Industry: Mining & Quarrying
Application: CEP-Centrifugal Pumps

Substrate: Cast Iron

Products: * Belzona 1111 (Super Metal),

* Belzona 1311 (Ceramic R-Metal) ,

* Belzona 1391 (Ceramic HT),

Problem

The equipment presented minor wear due to localized corrosion on the casing. It was necessary to restore the worn areas and apply a lining with excellent corrosion and high temperature resistance. The fluid consists of a caustic soda solution with few solids at a temperature of 81° C. Speed rotation: 1789 rpm.







Customer Location: Mine, Brazil

Application Date: May 2006



Photograph Descriptions

- * Equipment assembled before the repair,
- * Case refurbishment with Belzona 1111,
- * Case refurbishment concluded with Belzona 1111,
- * Service concluded, case lined with Belzona 1391 ,

Application Situation

Pump case.

Application Method

The repair and coating were carried out in accordance with Belzona Know-How System Leaflets CEP -3 & CEP-5. The surface was prepared by dry abrasive blasting at near white metal. After the surface preparation, Belzona 1311 was applied to rebuild the casing and Belzona 1111 was applied on the ring seating. After that, a single coat of Belzona 1391 was applied with a 600 to750 μ m thickness on the entire internal surface of the casing.

Belzona Facts

Belzona offered efficient repair and coating to pumps without the risk of distortion. Belzona 1391 offered excellent protection

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com



operating at 81°C.

www.belzona.com