Abrasion Control on Steel Bent Elbow Pipes with Belzona

ID: 5236

Industry: Steel & Metal Processing Customer Location: Mill, South Carolina
Application: VPF-Valves, Pipes and Fittings Application Date: September 2011

Substrate: Steel

Products: * Belzona 1391 (Ceramic HT),

Problem

Original steel pipes are built with a 2"x4" steel base that supports the bottom of the bent steel pipe. Heavy abrasion discharge from dust and mill operation particles penetrate the cylindrical steel wall surface and erode the base requiring pipe replacement or extensive welding.









Photograph Descriptions

- * Steel bent discharge pipe in operation,
- * Bent dust discharge pipe pre-drilled hole portal,
- * Bent dust discharge pipe filled with Belzona 1391,
- * Bent discharge pipe plugged prior to cure of 1391,

Application Situation

Support base of steel bent elbow pipes in a bag house exhaust room of a steel manufcturing facility.

Application Method

Base 2" x 4" x 8' in length had to have a portal hole drillled in order to pour the material and allow it to fill the cavity of the base. Belzona two part material was mixed and poured to fill spaces. Prior to full cure, the portal holes were filled with a screw that was additionally sealed by the Belzona 1391.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

Belzona Facts

The customer had not previously coated or filled the metal base of these bent elbow pipes. Consequently, it eroded from high pressure dust and mill exudate discharged from the cylindrical pipe and abrading it's way through the pipe and the base. This required an expensive pipe replacement every 18 months. Three years later, this pipe is still in service offering cost and maintenance savings for the customer.

www.belzona.com