BELZONA REPAIRS AND PROTECTS TAPERED SHAFT

ID: 5345

Industry: Mining & Quarrying Customer Location: Kettle Falls, WA, USA

Application: MPT-Mechanical Power Transmission Application Date: 1984

Substrate: Steel

Products: * Belzona 1111 (Super Metal),

* Belzona 9411 (Release Agent),

Problem

The tapered final drive shaft keyway was worn oversize and the shaft was worn down.









Photograph Descriptions

- * Tapered drive shaft showing wear on the keyway,
- * Shaft and keyway prepared and Belzona 1111 applied,
- * New tapered hub in place centering the key,
- * Bull dozer partially disassembled,

Application Situation

Bull dozer final drive shaft.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflet MPT-4. The keyway and tapered shaft was ground to roughen the surface. Belzona 9411 was applied to the new key and the new hub. Belzona 1111 was applied and the hub was mounted in place to center the key. The excess of Belzona 1111 was removed. After the cure, the machine was reassembled.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

Belzona Facts Replacing the shaft would require complete disassembly. A new shaft was not available.