BELZONA PROTECTS PIPE WITH INTERNAL LINING

ID: 5524

Industry: Oil & Gas Customer Location: Oil and Gas Company, BA, Brazil

Application: VPF-Valves, Pipes and Fittings Application Date: July 2009

Substrate: Carbon Steel

Products: * Belzona 1121 (Super XL-Metal),

* Belzona 5891 (HT Immersion Grade),

Problem

Since the operating fluid (produced water) is very corrosive, these pipes needed the internal protection in order to increase its working life.









Photograph Descriptions

- * Internal surface after blasting.,
- * Internal surface of the pipe coated with Belzona 5891.,
- * Close-up after the application of Belzona 5891.,
- * Overview of the pipelines.,

Application Situation

New pipes without an internal coating need protection to be put into operation.

Application Method

The weld seams and irregularities were roughened by grinding. The internal surface of the pipes was prepared by blast cleaning to a near white metal finish, SSPC SP-10 Sa 2½ standard. After the removal of residue and cleaning with a degreaser, Belzona 1121 was applied to smooth the weld seams/irregularities. Then the 1st layer of Belzona 5891 was applied at a thickness of 300-400 microns. After the initial mechanical stability of Belzona 5891, brush-off blast cleaning was carried out and the 2nd layer of Belzona 5891 was applied at a thickness of 300-400 microns. In the straight sections, the coating of Belzona 5891 was applied. Inspection was carried out and the identified misses were retouched.

Belzona Facts

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015
Belzona products are
FS 695214
manufactured under an ISO
ISO 14001:2015
9000 Registered Quality
EMS 695213
Management System.

www.belzona.com



cation.			