STRUCTURAL REINFORCEMENT TO NAPHTHA TOWER WITH BELZONA TECHNOLOGY

ID: 5577

Industry: Oil & Gas

Application:

Substrate: Carbon Steel coated with fiberglass
Products: * Belzona 1511 (Super HT-Metal) ,

* Belzona 1391 (Ceramic HT),

Problem

Leaking naphtha due to the presence of holes in the inferior generatrix.







Customer Location: Refinery, Brazil

Application Date: 2012



Photograph Descriptions

- * Naphtha leak at the lower generatrix,
- * Installation of the structural reinforcement of the cover with Belzona 1511 ,
- * Structural reinforcement installed in the lower generatrix with Belzona 1391 ,
- * Completed application,

Application Situation

Naphtha Accumulator

Application Method

The surface preparation was carried out through abrasive blasting of the pre-fabricated parts and grinding of the fiberglass substrate and metal parts of the equipment. Then, Belzona 1511 was applied to the upper generatrix with a stainless steel reinforcement sheet for fastening the tie rods and sealing the plates of the lower generatrix. Belzona 1391 was injected in the lower generatrix for a better accommodation with regards to the peripheral imperfections of the fiberglass.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

Belzona Facts

The naphtha accumulator has been previously repaired with fiberglass, a procedure that was not effective and displayed holes in the fiber. Belzona guaranteed to enclose the system with an operating temperature of 115°C and operating pressure of 400 gf/cm², exceeding several critical points, such as the location of the accumulator at the top of the tower at 86 m in height and hoisting 70 kg parts to the top. Inspection was carried out in February of 2015 and it was verified that the installed system is still working well.