

BELZONA REPLACES PTFE LINING AND CUTS DOWNTIME

ID: 5655

Industry: *Chemical & Petrochemical*
 Application: *TCC-Tanks and Chemical Containment Areas*
 Substrate: *Steel*
 Products: ** Belzona 1593 ,*

Customer Location: *Chemical Plant, Ferrara, Italy*
 Application Date: *April, 2015*

Problem

The original hot applied PTFE Lining required maintenance due to localised disbondment. The plant was facing a long downtime as it was not possible to conduct an in-situ repair of such a lining. The customer was looking for a solution that was faster and easier to apply.



Photograph Descriptions

- * PTFE lining removed ,
- * Belzona lining applied ,
- * Coating thickness measured ,
- * Inspected after 6 months in service ,

Application Situation

Reactor operating between 70°C and 80°C at a Polyolefins petrochemical plant. Process fluids included salt, caustic and titanium tetrachloride.

Application Method

The application was carried out in accordance with Belzona Know-How System Leaflet TCC-5 for protecting and rebuilding steelwork. After grit blasting to SA 2.5, a two-coat system of Belzona 1593 was hand applied to an area of 25 m².

Belzona Facts

Belzona was chosen to replace PTFE as it reduced downtime from weeks to days and was also much easier to apply. Any future

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
 FS 695214
 ISO 14001:2015
 EMS 695213

Belzona products are
 manufactured under an ISO
 9000 Registered Quality
 Management System.

www.belzona.com

BELZONA
 Repair • Protect • Improve

mechanical damage will be repairable in-situ.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

