## RISER BOOT TOPPING PROTECTED WITH BELZONA

ID: 5668

Industry: Oil & Gas Customer Location: Production Platform, North Sea, UK

Application: SOS-Ships and Offshore Structures Application Date: July 2015

Substrate: Steel, Neoprene

Products: \* Belzona 1321 (Ceramic S-Metal),

\* Belzona 3411 (Encapsulating Membrane), \* Belzona 3911 (PSC Surface Conditioner),

#### **Problem**

The customer required an isocyanate-free flexible system to provide excellent protection against corrosion in this harsh environment. The repair had to be applied in-situ.







### **Photograph Descriptions**

- \* Substrate prepared for application,
- \* Application of the first layer of Belzona 3411,
- \* Completed application,

# **Application Situation**

The square edge of the previously used Neoprene sheet allowed water to sit on the edge and penetrate underneath the sheet, resulting in severe corrosion.

#### **Application Method**

The application was carried out in accordance with a modified version of Belzona Know-How System Leaflet SOS-21. After cutting back the loose Neoprene cladding and preparing the surfaces, Belzona 1321 was applied to the steel riser and blinded with Belzona 9231 (Surefoot Aggregate) to provide an anchor pattern for the application of Belzona 3411. Belzona 3911 was applied onto the Neoprene to achieve adhesion before the Belzona 3411 system was applied to bridge over the steel/neoprene junction. A bond breaker tape was applied at the junction to optimise movement at this point.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

### **Belzona Facts**

The customer was pleased with the Belzona solution as the repair could be carried out in situ using the rope access technique. The cold curing Belzona 1321 and 3411 system are isocyanate-free and provide a quick and safe application offering long term corrosion protection.

www.belzona.com