FGD AGITATOR BLADE REPAIR IS NO PROBLEM FOR BELZONA 2111

ID: 5844

Industry: Power Customer Location: Power Plant, Illinois, USA

Application: FBC-Fans, Blowers and Compressors Application Date: Fall 2014


Substrate: Steel

Products: * Belzona 2911 (Elastomer QD Conditioner),

* Belzona 2111 (D & A Hi-Build Elastomer),

Problem

Old blades were starting to delaminate and the rubber was holed through and fatigued









Photograph Descriptions

- * Old blades.
- * Blades with 1st coat of Belzona 2111,
- * Thickness being achieved,
- * Finished product with holes being uncoated so that Belzona 2111 could be applied to the bolts after they were installed,

Application Situation

The Customer was looking for a long-term solution and repair for their agitator blades that are used in lime slurry for their FGD.

Application Method

The surface of the new blades was prepared by sandblasting to a near white metal finish. Then, Belzona 2911 was applied with several coats of Belzona 2111 to achieve a thick and slick uniform finish.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA®

Belzona Facts The Belzona solution proved to be the right choice for the customer as the application took half the time needed for replacement and our repair was less expensive. Belzona has had previous success with elastomer repairs in other areas of the FGD.

www.belzona.com