

BELZONA REPAIRS IRRIGATION HOSE

ID: 5916

Industry: General Industry
Application: VPF-Valves, Pipes and Fittings
Substrate: ABS Plastic
Products: * Belzona 2111 (D & A Hi-Build Elastomer) ,
* Belzona 2911 (Elastomer QD Conditioner) ,
* Belzona 9341 (Reinforcement Sheet) ,

Customer Location: Northwestern Washington, USA
Application Date: September 2015

Problem

A small crack formed from hose working on and off the reel.



Photograph Descriptions

- * Hose lifted to a working height. ,
- * Roughing brush used to obtain a rough surface profile. ,
- * Belzona 2111 with Belzona 9341 applied over the conditioner. ,
- * Completed application. ,

Application Situation

Plastic irrigation hose uncoiled from its reel in the field.

Application Method

The pipe was lifted to working height for preparation and application. Then, the pipe was scuffed with a roughing brush for 2 inches on both sides of the crack. The pipe was conditioned before applying a layer of gelled Belzona 2111, followed by Belzona 9341 and an overcoat of Belzona 2111.

Belzona Facts

Both mechanical couplings and high temperature fusings have been tried and failed. The customer has had other successful repairs for conveyor belts with Belzona and selected another Belzona solution.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

