# BELZONA STATIC DISSIPATIVE LINING FOR CHEMICALLY AGGRESSIVE ENVIRONMENT

ID: 6016

Industry: Chemical & Petrochemical Customer Location: Refinery, France
Application: TCC-Tanks and Chemical Containment Application Date: April 2012

Areas

Substrate: Carbon Steel

Products: \* Belzona 4311 (Magma CR1) < br /> Belzona 4351 (Magma CR5),

#### **Problem**

The client required a coating combining high chemical resistance and static dissipative characteristics in order to comply with safety regulations and eliminate the risk of tank's contents igniting.









# **Photograph Descriptions**

\* 1. Scaffolding assists Belzona 4311 application <br />2. First layer of Belzona 4311 applied <br />3. Application of the lining on the floor <br />4. Application of Belzona 4351 completed ,

### **Application Situation**

One of the world's largest plastics, chemicals and refining companies required lining for storage tank containing chemical mixture including Xylene and Sulphuric acid at maximum temperature of 70°C.

### **Application Method**

The application was carried out in accordance with Belzona Know-How System Leaflet TCC-5. After thorough surface preparation, a two layer system of Belzona 4311 was applied throughout the tank. Finally, across the tank's entire bottom and half a metre up the walls, the application was finished with a coat of Belzona 4351. Note that Belzona 4351 was sufficiently grounded.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

## **Belzona Facts**

Scaffolding was installed allowing for safe and effective application even at the full height of the tank. This solution reduced downtime, meaning the tank could be put into service in a very short time. Belzona system provided the required level of acid resistance combined with the need for static dissipation.

www.belzona.com