

BELZONA REFURBISHES TRAIN DIESEL TANK

ID: 6066

Industry: Transport
Application: TCC-Tanks and Chemical Containment Areas
Substrate: Steel
Products: * Belzona 1121 (Super XL-Metal) ,

Customer Location: Leicestershire, UK
Application Date: 2015

Problem

Moisture was entering the gap between the steel tank and the fibreglass coating, resulting in corrosion damage and leading to pitting and holes.



Photograph Descriptions

- * The corroded diesel tank before treatment ,
- * Lower portion of the tank prior to treatment ,
- * Tank plate-bonded with Belzona 1121 and coated in GRP ,
- * Repaired tank refitted to train ,

Application Situation

Steel diesel tank originally coated in fibreglass in order to protect the metal against sparks.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflet TCC-1. The fibreglass coating was grit blasted away. Metal plates were then cold bonded over the defects using Belzona 1121 and the tank then re-coated with GRP, painted black and refitted onto the trains.

Belzona Facts

This solution allowed the company to avoid hot repair weld techniques. Following initial application, Belzona 1121 has been incorporated into the client's specified solution for diesel tank repairs and is now a company approved repair method.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA[®]
Repair • Protect • Improve