BELZONA STOPS COSTS SPIRALLING OUT OF CONTROL

ID: 6076

Industry: General Industry Customer Location: Pigment Manufacturer, UK

Application: TCC-Tanks and Chemical Containment Application Date: 2010

Areas

Substrate: Carbon Steel

Products: * Belzona 4311 (Magma CR1),

Problem

An unwanted reaction within these assets is the formation of hot hydrochloric acid, which was then attacking the steel spirals. It was thought that there were only a few weeks left before the heat exchanger would fail. The lead time on a replacement was nearly 12 months.









Photograph Descriptions

- * One end of spiral heat exchanger untreated,
- * Belzona 4311 application underway,
- * Close up of coating,
- * Completed application,

Application Situation

Spiral Heat Exchangers commonly used within part of the client's facilities.

Application Method

The steel was grit blasted, followed by a brush application of 3 coats of Belzona 4311 in accordance with Belzona Know-How System Leaflet TCC-5.

Belzona Facts

The replacement cost for this heat exchanger was over £230,000. Belzona was used to coat the affected areas on both ends of the asset with a material that can withstand hydrochloric acid, even at 60°C. The whole application was completed with only minor material costs of about £600. The client then repeated the application on a further two identical spiral heat exchangers the

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

following year.

www.belzona.com