

BELZONA PROTECTS INTERNAL OF CHP STACK

ID: 6335

Industry: Pulp & Paper
Application: TCC-Tanks and Chemical Containment Areas
Substrate: Mild Steel
Products: * Belzona 1593 ,

Customer Location: Papermill, Scotland, UK
Application Date: May 2016

Problem

The stack had been experiencing corrosion issues from the chemicals within the flue gas stream. It was suspected that acids within this stream were condensing on the vertical wall of the stack & causing excessive corrosion around the localized area. Repairs had been attempted in the past by welding mild steel plates to the internals of the stack during shutdowns. This did not solve the problem & the base issue kept occurring year after year.



Photograph Descriptions

- * 1. CHP Stack ,
- * 2. Plates welded in place during previous attempted repairs ,
- * 3. Base of the stack coated ,
- * 4. completed Belzona 1593 coating ,

Application Situation

The stack of the plants CHP (Combined Heat & Power) unit

Application Method

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve

Application was carried out in accordance with Belzona System Leaflet TCC-5. After grit blasting the surface a paste grade Belzona was used to smooth out pitting before applying a two coat system of Belzona 1593.

Belzona Facts

The Belzona solution solved the problem & kept the metal loss from reoccurring. All the work was carried out during a short shutdown.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

