BELZONA STRENGTHENS REFUGE ON OFFSHORE PLATFORM

ID: 6346

Industry: Oil & Gas Customer Location: Gas platform, Southern North Sea, UK

Application: GSS-Gaskets, Seals and Shims Application Date: February 2013

Substrate: Steel

Products: * Belzona 4111 (Magma Quartz),

Problem

Severe corrosion had caused pitting with some penetrations through the roof reducing the integrity of the refuge. refuge had to withstand a blast load of 0.25 bar. As this is an active gas storage unit welding was not an option for repairs.









Photograph Descriptions

* 1. General view of the roof 2. Positioning doubler plate onto Belzona 4111 3. Plates bonded where access was restricted 4. Completed application ,

Application Situation

Roof of refuge used in case of accident.

Application Method

Application was carried out in accordance with a modified Belzona Know-How System GSS-9. A slurry mix of Belzona 4111 was used to bed steel doubler plates to cover the roof of the refuge. Penetrations through the roof were initially sealed with small plates bonded in place with Belzona 1211. A fire protection coating was finally applied to provide the required fire rating.

Belzona Facts

All safety factors were considered during the design of this repair which was carried out without the need for hot work. Access to several areas of the roof were limited to 500mm head room, so ease of application of the Belzona system was very important.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015

Belzona products are
FS 695214

ISO 14001:2015

Belzona products are
manufactured under an ISO
9000 Registered Quality
EMS 695213

Management System.

BELZONA®
Repair • Protect • Improve