

BELZONA CORROSION PROTECTION FOR CO2 ABSORBER TOWER

ID: 6424

Industry: General Industry Customer Location: Nitrogen Fertilizer Plant, Bulgaria

Application: TCC-Tanks and Chemical Containment Application Date: August 2014

Areas

Substrate: Carbon Steel

Products: * Belzona 1311 (Ceramic R-Metal),

* Belzona 1391 (Ceramic HT),

Problem

Significant defects of the inner walls and the bottom of the absorber due to corrosion and erosion in the presence of aggressive chemicals such as MDEA & MEA at elivated temperatures ($80-100^{\circ}\text{C}$).









Photograph Descriptions

- * 1. Inspection in 2016 of the linning applied in 2014,
- * 2. View of the pad welded defect areas,
- * 3. View of repair with Belzona 1311,
- * 4. The final application with Belzona 1391,

Application Situation

60 metre tall process CO2 absorber tower required corrosion protection

Application Method

The applications were carried out in accordance with Belzona Know-How Leaflet TCC-3. The customer pad welded deeply pitted areas. Less damaged areas were filled and smoothed with Belzona 1311 before coating with Belzona 1391.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com



Belzona Facts

The process tower had worked previously without internal linning until the discovery of major erosion / corrosion defects. The first application of Belzona was carried out in 2014 and the condition was inspected every year. The last inspection in 2016 has reported no degradation of Belzona linning.

www.belzona.com