

FULL PROTECTION OF DEHYDRATOR WITH BELZONA LINING AND NOZZLE INSERTS

ID: 6449

Industry: Oil & Gas
Application: TCC-Tanks and Chemical Containment Areas
Substrate: Carbon Steel
Products: * Belzona 1391T ,

Customer Location: Oil & Gas Asset Owner, China
Application Date: December 2016

Problem

Newly fabricated vessel which was required to have an internal protective coating.



Photograph Descriptions

- * 1. Grit blasting to Near White Metal cleanliness levels ,
- * 2. Placing the nozzle inserts ,
- * 3. Application of the second coat ,
- * 4. Inspecting for holidays or discontinuities via spark testing ,

Application Situation

This dehydrator needed full internal protection, which included a Belzona fit-for-service lining and Belzona inserts for small bore nozzles. The vessel was designed for operating temperature levels of 20C (68F) minimum, 58 C (136 F) normal, and 70 C (158 F) maximum. The chemical service was crude oil, water and sour gas.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflet TCC-5 and TCC-16b . Pre-formed nozzle inserts were fabricated and bonded into small bore nozzles to ensure continuity of protection.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

BELZONA
Repair • Protect • Improve

Belzona Facts

Using the Belzona internal coating and nozzle inserts solution, the vessel will have a longer service life.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015

FS 695214

ISO 14001:2015

EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

