BELZONA PROTECTS FLANGES OF CONCRETE LINED PIPEWORK

ID: 688

Industry: Power Customer Location: Power Station, Germany

Application: VPF-Valves, Pipes and Fittings Application Date: August 2002
Substrate: Concrete and Carbon Steel

* Belzona® 1111 (Super Metal), * Belzona® 9411 (Release Agent),

Problem

Products:

The cutting of the pipes damaged the concrete lining and would have resulted in crevice corrosion on the flange face and corrosion creep under the concrete. It was not practical to repair the concrete with more concrete.









Photograph Descriptions

- * Blasted steel flange face note concrete lining also prepared ,
- * Use of formers as per VPF-13.,
- * Completed application ,
- * Inspection after 3 years service,

Application Situation

Installation of additional valves into concrete lined cooling water pipework (ranging from 400-1200mm)

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflets VPF-3, -13.

Belzona Facts

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA

www.belzona.com

Fourteen Flanges were protected and all works completed within two days. The cooling water system operates with a maximum pressure of three bar. After inspection following three years service, the satisfied client has specified the use of Belzona 1111 for other damaged concrete lined pipes



ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.



www.belzona.com