# **Belzona Protects Blades Effectively against Abrasive Pulps**

ID: 7485

Industry: Mining & Quarrying

Application: SHM-Solids Handling Machinery

Substrate: Carbon steel
Products: \* Belzona 1812,

Problem

Severe blade abrasion



Application Date: February 2016







## **Photograph Descriptions**

- \* 1. Initial repair by welding.,
- \* 2. Blades protected with Belzona 1812,
- \* 3. Blades inspected after 12 months in service,

### **Application Situation**

Pulp-agitator blades in the chemical section of the phosphate mine.

## **Application Method**

After removing the remainder of the rubber coating, the blades were welded on the heavily damaged areas. The surface was then grit-blasted before the application of Belzona 1812 according to the SHM-13 Belzona procedure.

#### **Belzona Facts**

Previously, the mine had to shut down the tank every month to replace the rubber-coated blades. Once coated with Belzona 1812, the blades were inspected after 12 months in service and were in good condition, requiring some retouching on about 10% of the surface: In 2017. the customer asked for a repair of 16 blades for other storage tanks.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015

Belzona products are
FS 695214

ISO 14001:2015

Belzona products are
manufactured under an ISO
9000 Registered Quality
EMS 695213

Management System.

BELZONA®
Repair • Protect • Improve