Belzona Seals Wind Turbine Tower Base Against Water Ingress

ID: 7500

Industry: Power Customer Location: Wind Farm, West Texas, USA

Application: WPA-Wall Problem Areas Application Date: Summer 2016

Substrate: Concrete and Metal

Products: * 3111 (Flexible Membrane), * 3911 (PSC Surface Conditioner),

Problem

Rain water and moisture seeps into the ground and into the wind turbine structure through the base around the tower structure. This over time affects the concrete base and propagates cracks and corrosion at the base of the tower. In this case the current coating failed due to UV degredation leading to delamination from the concrete surface.









Photograph Descriptions

- * 1. The old coating that failed, yellowing and peeling from the concrete surface. ,
- * 2. The application area being outlined.,
- * 3. Application of Belzona 3111 underway. ,
- * 4. Application completed and tower base sealed with Belzona 3111. ,

Application Situation

Wind Power Tower Base

Application Method

The application was carried out in accordance with a modified version of Belzona System Leaflet WPA-1.

Belzona Facts

Belzona 3111 was a great and easy way to seal the base of the structure and the concrete. The application was simple to do and

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

gave the Customer that extra flexibility in that area. Short of sealing with some type of concrete filler they had few options for this problem. Sealing the tank base with Belzona 3111 proved to be a cost-effective solution with minimal downtime and interruption to the operation of the turbine.	



ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

