Belzona Cuts Down a Concrete Shimming Application Time from 45 to 7 days

ID: 7741

Industry: Pulp & Paper

Application:

Concrete

Substrate: Products:

* Belzona 4111 (Magma-Quartz),

* Belzona 4151 (Magma-Quartz Resin),

Problem

Due to constant movement and vibration created between the skid and the concrete foundation, the heads of the bolts holding the base down started to break off.







Customer Location: Paper Mill, Brazil

Application Date: August 2017



Photograph Descriptions

- * View of the Crane,
- * Concrete foundation before,
- * Application in progress including new anchor holes being drilled,
- * Completed application,

Application Situation

A crane's base was seeing the heads of the bolts holding it down beginning to break off.

Application Method

First, 48 new holes were drilled to install newly fabricated bolts. Then the skid was positioned over the concrete base, secured and aligned with 4 metal bars in 4 points around the perimeter of the skid, and positioned on top of the concrete base. Belzona 4111 and Belzona 4151 were then mixed and injected into each of the holes. Anchor bolts were inserted, and excess of product was used to fill the annular space under the equipment.

Belzona Facts

A traditional approach to problems like this one would require at least 45 days to demolish the base of the crane and reconstruct it again. Whereas the Belzona solution came at half the cost of the traditional method and promised to return the crane back to

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 FS 695214 manufactured under an ISO ISO 14001:2015 9000 Registered Quality EMS 695213 Management System.

service in 7 days. condition.	The customer was very impre	ssed with the application	and one year later rep	orted that the bases w	ere in perfect
For more examples of	Belzona Know - How In Action, please	e visit https://khia.belzona.com			