H2S Damaged Lift Station Rebuilt and Protected with Belzona

ID: 7812

Industry: Buildings & Structures Customer Location: Florida, USA
Application: TCC-Tanks and Chemical Containment Application Date: Spring 2018

Areas

Substrate: Concrete

Products: * Belzona 1212,

* Belzona 4131 (Magma-Screed), * Belzona 4141 (Magma-Build), * Belzona 4911 (TX Conditioner), * Belzona 5811 (immersion Grade),

Problem

Concrete had no previous protective coating and showed damage due to H2S.









Photograph Descriptions

- * 1. Training of the application crew.,
- * 2. Technicians applying Belzona 4911.,
- * 3. Application of Belzona 4131 (Magma-Screed).,
- * 4. Final coat of Belzona 5811.,

Application Situation

A lift station suffered from H2S damage.

Application Method

The application was carried out in accordance with modified versions of TCC-9 and TCC-15. Preparation consisted of pressure washing and blasting the concrete to clear out any loose or H2S damaged concrete. Belzona 4911 (TX Conditioner) was applied. NOTE:(a small ground water leak had formed during the application of Belzona 4911, Belzona 1212 was used from a supplied Belzona 1212 emergency kit with reinforcement sheet rolled up and pressed into the hole and sealed with more Belzona 1212 over it - this repair stopped the ground water and we continued the application of Belzona 4911). Then, Belzona 4131 (Magma-Screed) was applied to the walls. NOTE:(Belzona 4141 was used if the damaged was greater then 1/4" on the walls and applied to the ceiling of the lift station). Belzona 5811 was applied as a two-coat system.

Belzona Facts

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA

erformance of Belzona products from past Know-How in Action case studies presented.	