Belzona alters yacht window frames with ease

ID: 7949

Industry: Marine Customer Location: Mallorca
Application: GSS-Gaskets, Seals and Shims Application Date: June 2018

Substrate: Steel

Products: * Belzona 1121,

Problem

Due to a last minute design change affecting the thickness of the installed glass, the window frames had to be modified. As the structure had already been built, it was not possible to alter the structural design, and therefore an after market alteration had to be made so that the window frames could accommodate the lower thickness windows.









Photograph Descriptions

- * 1. General view of window frames,
- * 2. Surface being prepared for application,
- st 3. Belzona applied with formers in place ,
- * 4. Completed application,

Application Situation

A newly built yacht window installation without 216 linear meters of window frame.

Application Method

The application was carried out in accordance with a modified version of Belzona System Leaflet GSS-9. Belzona 1121 was used to build up the thickness of the window frames by 1 - 1.5 cm. A forming technique was used to ensure precise tolerances. Belzona 9411 (Release Agent) was applied to the formers so that they could be easily removed after the Bezlona 1121 had cured.

Belzona Facts

Belzona 1121 was selected due to it's high build capability, allowing the required thickness to be added to the window frames in a single application. The Belzona material is 100% solids, meaning that it will not distort or shrink whilst curing. This is essential to ensure the correct tolerances can be met. Welding was considered, but rejected as it was deemed the heat stresses could damage

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

me, meaning the applicati			