

Belzona® Composite repair On-site Application for Buried Natural Gas Pipelines

ID: 8242

Industry: Oil & Gas
Application: VPF-Valves, Pipes and Fittings
Substrate: Carbon steel
Products: * Belzona 1161 (Super UW-Metal) ,
* Belzona 9371 (Reinforcement Sheet) ,

Customer Location: Sichuan, China
Application Date: August, 2013

Problem

The operating pressure of these buried gas pipelines is 2Mpa; Maximum depth of external metal loss is 6.7mm; The corrosion area is 40 × 60mm. These pipelines have been immersed in a humid environment for a long time, and the surface of the pipeline cannot be dried.



Photograph Descriptions

- * 1. Buried pipeline,
- * 2. Damaged external surface,
- * 3. Dry wrapping of the reinforcing sheet;
- * 4. Application complete ,

Application Situation

These natural gas supply pipelines are used for the local scenic area which cannot be replaced or shut down. The client requires on-site repair by an engineering designed repairing system.

Application Method

Application carried out in accordance with Belzona System Leaflet VPF-11

Belzona Facts

As these buried gas pipelines operate in humid environments (such as paddy fields and hills area), Belzona moisture tolerant material is used for on-site application which avoids hot-work and saves time and costs for client. The client is very pleased with the result.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA®
Repair • Protect • Improve