Belzona 1251 Prevents Major Plant Shutdown

ID: 8281

Industry: General Industry Customer Location: Western Australia

Application: TCC-Tanks and Chemical Containment Application Date: May 2020

Areas

Substrate: Carbon Steel

Products: * Belzona 1251 (HA-metal),

* Belzona 9341 Reinforcement Tape,

Problem

The original wall thickness was 9.56(mm) The current thickness is around 3mm in different spots and unable to UT the weld before the neck. This is on live equipment and due to the location of the spool rope access was required.









Photograph Descriptions

- * Spool location ,
- * Spool condition prior to repair,
- * Repair using 1251 and 9341,
- * Repair using 1251 and 9341,

Application Situation

400NB Spool on the client's Cyclone Feed Line with an operating temperature of 80(°C) running Caustic Slurry. The pipeline in question is critical to the client, if it failed, it would mean the plant would be at half capacity.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

Application Method

A DRY wrap of the 9341 reinforcement tape was used to determine how much was required. A thin layer of Belzona 1251 was applied to all prepared areas pushing it well into the surface. We then Wet out a length of Belzona® 9341 with Belzona 1251. The tape coated side down to the repair was wrapped firmly around the pipe until 1251 is forced through to the outer surface. We applied a further layer of Belzona 1251 at approximately 6mm thick to completely seal the surface.

Belzona Facts

As a replacement for this spool was not possible due to the plant having an unplanned shutdown, a repair to this spool was critical. If it had ruptured it would have shut down 50% of the site's operation.

www.belzona.com