Belzona prevents wear on an ash slurry mixer

ID: 8555

Industry:PowerCustomer Location:WashingtonApplication:SHM-Solids Handling MachineryApplication Date:February 2021

Substrate: Steel

Products: * Belzona 1331,

* Belzona 1813 ,

Problem

The paddles on their ash slurry mixer would wear down to less than half of their original length in 3 months forcing them to be replaced. The original paddles were made from hardox steel. The mixer box and shafts had some mild wear and corrosion as well









Photograph Descriptions

- * 1. Original condition,
- * 2. Box coated with Belzona 1331,
- * 3. Shafts coated with Belzona 1331,
- * 4. Paddles being coated with Belzona 1813,

Application Situation

Cogen powerplant ash slurry mixer

Application Method

The mixer box and shafts were grit blasted and the Belzona 1331 was applied in two layers by hand. The new mixer paddles were hand ground and the Belzona 1813 was applied by hand.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.



Belzona Facts

The original method of replacing the paddles was causing thousands of dollars in new blades, man hours, and shutdowns every three months. By using this Belzona solution, the mixing box and paddles have been in operation for over six months with absolutely no sign of any wear. In six months, the cost of the Belzona solution has already been more than paid for.

www.belzona.com