# BELZONA SUPERWRAP II RETURNS PIPING BACK TO SERVICE IN 48 HOURS

ID: 8577

Industry: Oil & Gas Customer Location: Western Australia
Application: VPF-Valves, Pipes and Fittings Application Date: October 2020

Substrate: Carbon Steel

Products: \* Belzona 1983 (SuperWrap II Resin),

\* Belzona 9381 (SuperWrap II Reinforcement Sheet),

\* Belzona 9382 (Release Film),

#### **Problem**

The 220mm diameter pipe had developed a critical (Class 3) thin wall defect at the bend. The operating temperature was 95°C and the operating pressure was 10 bar. The total defect length was 280mm in axial.









# **Photograph Descriptions**

- \* 1. Measuring the corroded pipe,
- \* 2. Wetting out the Reinforcement Sheet,
- \* 3. Wrapping the pipe,
- \* 4. Applying the Release Film over the wrap,

### **Application Situation**

High Temperature, Hydrocarbon Piping

# **Application Method**

The application was completed in accordance with Belzona Know-How System Leaflet VPF-11. The defect area was abrasive blasted to SA 2.5 with a 75 microns profile. Belzona SuperWrap II was applied in accordance with the engineered design as a 6 wrap system, using Belzona 1983 resin to provide a further 12 years service life.

### **Belzona Facts**

Belzona SuperWrap II was chosen because it is an engineered solution that can be designed as a pipe repair system, and is compliant with both ISO 24817 and ASME PCC-2. With the customer able to do their own designs and having applicators on-site, the repair was completed within 48 hours.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA