

Rubber Lining on Limestone Filter Tank Replaced with Belzona's Epoxy Lining


ID: 9006

Industry: Power
Application: TCC-Tanks and Chemical Containment Areas
Substrate: Carbon steel
Products: Belzona 1111 (Super Metal), Belzona 1321 (Ceramic S-Metal)

Customer Location: Ras Laffan, Doha, Qatar
Application Date: June 2016

Problem

Cracks, blisters, delaminations and alligatoring were found in the existing rubber lining of the tank after a long period of use without maintenance.



Cracking on the original rubber lining



Delaminations on the original rubber lining



Initial coat of Belzona 1321 being applied



Application completed and protected tank inner surfaces

Application Situation

A patch repair option of the rubber lining was replaced by the use of Belzona rebuilding paste grade and protective coating.

Application Method

Damaged areas of the existing rubber lining were removed and the exposed metal surface was grit blasted. Exposed deeply pitted areas were filled with Belzona 1111 and rebuilt up to 1 mm to compensate for metal loss. Multiple coats of Belzona 1321 were applied by brush for extra protection.

Belzona Facts

The Belzona solution is easy to install and has been proven in service to last longer than conventional rubber linings applied to tank inner surfaces. It is also cost-effective, requiring less equipment to apply and the usual manpower required to restore the wall thickness and apply the protective coating.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve

Copyright © Belzona International Limited 2024