

BELZONA® 2141 PROTECTS FRANCIS TURBINE RUNNERS FROM CAVITATION

ID: 901

Industry: Power
Application: CEP-Centrifugal Pumps
Substrate: Cast Iron
Products: * Belzona® 2141 (ACR-Fluid Elastomer) ,
* Belzona® 2941 (Elastomer SP-Conditioner) ,

Customer Location: Hydroelectric plant (Ontario, Canada)
Application Date: August 1998 and July 2001

Problem

Cavitation had caused erosion of the parent metal and loss of performance of the turbine. Belzona® 1341 and Belzona® 1421 had been applied in 1998 but had suffered erosion in this aggressive environment.



Photograph Descriptions

- * Cavitation damage ,
- * Belzona® 1341 (left) and Belzona® 1421 (right) after 36 months service ,
- * Belzona® 2141 after application ,
- * Belzona® 2141 after 34 months ,

Application Situation

Twin 914mm (36 inch) Francis Turbine Runners operating with 13m (42 feet) head and constructed in 1945.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflet CEP-3.

Belzona Facts

Inspection of the Belzona® 2141 in 2002 showed no damage – further inspection after 34 months showed no sign of damage to the coating.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA®
Repair • Protect • Improve