

# Flange Rebuilding at a Fertilizer Plant

ID: 9156

Industry: Chemical & Petrochemical

Customer Location: Barranquilla, Colombia

Application: VPF-Valves, Pipes and Fittings

Application Date: May 2017

Substrate: Carbon steel

Products: Belzona 1111 (Super Metal), Belzona 1161 (Super UW-Metal)

## Problem

There was evidence of bimetallic corrosion and erosion in the 24" elbow between the flange and the seal, which was perforated and thinned the thickness of the flange.



View of damage to the flange

Surface preparation.

Final application.

## Application Situation

Minimum surface preparation to apply Belzona 1161 was key to save time and money.

## Application Method

A thin layer of Belzona 1161 was rubbed over the entire damaged surface, then Belzona 1111 was applied to recover thickness and fill the holes produced by erosion.

To maintain the diameter of the holes through which the bolts pass, it was necessary to cut some tubes to be used as molds and thus maintain the original measurements.

## Belzona Facts

Quick and localized repairs were carried out with Belzona putting the equipment back into service as soon as possible.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015

Belzona products are

FS 695214

manufactured under an ISO

ISO 14001:2015

9000 Registered Quality

EMS 695213

Management System.

[www.belzona.com](http://www.belzona.com)

**BELZONA**  
Repair • Protect • Improve