

# Belzona Restored and Protected the Oil Sealing Surface of Wind Turbine

ID: 9607

**Industry:** Power**Application:** FBC-Fans, Blowers and Compressors**Customer Location:** Yunnan, China**Application Date:** August 2023**Substrate:** Carbon steel**Products:** Belzona 1311 (Ceramic R-Metal)**Problem**

The oil sealing surface of a wind turbine at the wind farm were worn out and needed to be repaired.



Full view of wind turbine



Sealing face before repair



During application



Application finished

## Application Situation

The operating temperature was ambient. Wind farms were very windy and the sealing surface of the wind turbine was heavily abraded.

## Application Method

The application was carried out in accordance with Belzona Know-How leaflets FBC-05. Surface preparation was carried out by grinding with an angle grinder, followed by repair and protection of the sealing surfaces with Belzona 1311.

## Belzona Facts

After four months of use, no leaks were seen in the inspection and the client was very satisfied with the results. This solution greatly reduced the cost of replacement for the client, as well as downtime.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015

FS 695214

ISO 14001:2015

EMS 695213

Belzona products are  
manufactured under an ISO  
9000 Registered Quality  
Management System.

[www.belzona.com](http://www.belzona.com)