

BELZONA 1814 SCREW CONVEYOR PROTECTION

ID: 9652

Industry: *Water / Wastewater*
Application: *SHM-Solids Handling Machinery*

Customer Location: *United Kingdom*
Application Date: *November 2019*

Substrate: *Carbon steel*
Products: *Belzona 1814*

Problem

Screw conveyor used to skim sludge from the base of a silo at a biomass plant.



Initial condition



After Belzona 1814



After Belzona 1814

Application Situation

High abrasion was leading to unprotected screws only lasting 3-4 months in service. Previous Belzona applications on this type of screw was completed with Belzona 1812, which extended their life to over 2 years.

Application Method

The screw conveyor was grit blasted to SA2 1/2 with a minimum surface profile of 3 mil (75 microns). The area to be coated was then cleaned and degreased using Belzona 9111. Belzona 1814 was applied to the entire area of the conveyor to provide long-term protection against heavy abrasion.

Belzona Facts

The client was keen to try Belzona 1814 on their latest screw conveyor as had previously had success with Belzona 1812

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA[®]
Repair • Protect • Improve