Cracked coke gas pipe

ID: 9848

Industry: Steel & Metal Processing Customer Location: Middle of Sweden Application: VPF-Valves, Pipes and Fittings Application Date: May 2024

Substrate: Carbon steel

Products: Belzona 1212, Belzona 1391T, Belzona 1511 (Super HT-Metal)

Problem

The customer had problems cracking and leaking. This had to be both sealed and reinforced. Hot work was not possible as the pipe transports combustible gases. This process could not be shut down, so we had to find a solution together with the customer to be able to perform this during operation.

Our solution was to perform this using a mechanical clamp together with grouting the space between the pipe and clamp with Belzona 1391T. This sealed and fixed the area to ensure it was tight and able to withstand future movement in the area.









Here we have the area with the Here the crack is clearly visible Installation of the crack, tar has leaked out and at after blasting. We have drilled the moment the pressure is reduced so no smoke is leaking to minimise the risk of the out

holes at the ends of the crack crack moving on.

reinforcement plate and with Belzona 1511

Injecting with Belzona 1391T to fill the space between the clamps and sealing of the edges sheet and the pipe. We started at the bottom and worked our way up. This way we both bond and seal the whole system.

Application Situation

Given the circumstances and the fact that they were unable to decommission the equipment, there were major benefits both in terms of time and cost savings. We did it with a cold method during full operation

Application Method

Prior to this project, a site visit was made to identify the damage, and to measure what the reinforcement sweep would look like. Once on site, we blasted the area to see the damage in its entirety and drilled holes at the ends of the crack to prevent it from

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are FS 695214 manufactured under an ISO ISO 14001:2015 9000 Registered Quality EMS 695213 Management System.

travelling further. Patched the damage with Belzona 1212. Welded off the area again and the sheet metal sweep. Fitted the sheet metal sweep. Patched the edges with Belzona 1511 to prevent leakage during injection with Belzona 1391T.

Belzona Facts

The cost saving is difficult to evaluate as they cannot run down operations. But if they had been able to shut down, they would have lost large sums per hour

www.belzona.com